Trade name : Revision date : Print date :		Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020	Version :	1.0.0
SEC	TION 1: Ident	ification of the substance/mixture an	d of the company/ underta	aking
1.1	Product iden	tifier		
	•	+ Fixer concentrate		
1.2	Relevant ide	ntified uses of the substance or mixtu	re and uses advised agains	st
		entified uses		
	• •	t for Dürr developers.		
	Products Cate PC 30 - Photo-			
	Uses advise			
		according to order.		
	Remark	-		
	The product is i	ntended for professional use.		
1.3	Details of the	supplier of the safety data sheet		
	Supplier (ma	anufacturer/importer/only representa	ative/downstream	
	user/distrib			
	orochemie Gmb			
		-Planck-Straße 27		
		city: 70806 Kornwestheim		
	•	+49 7154 1308-0		
	Telefax : +4			
		contact : DÜRR DENTAL SE, Höpfigheimer Str. 5-0, Fax: +49 7142 705-500, info@duerrdental.com	17, 74321 Bietigheim-Bissingen, Gern	nany
	DÜRR DENTAL SI Importer/Distribu	E, PO Box 2067, Woonona East New South Wales 251 tor:	· · · · · · · · · · · · · · · · · · ·	

Ivoclar Vivadent Ltd, PO Box 303011, North Harbour, Auckland, 0751, Phone +64 9 914 9999 Fax+64 9 914 9990

1.4 Emergency telephone number

NZ: National Poison Centre (New Zealand) 0800 764 766 Poisons Hotline (24 hours/7days)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Although there is no labelling required for this product, we nevertheless advise observation of the safety recommendations.

Classification according to GHS

None

Classification procedure

The classification was carried out according to the calculation method of GHS.

2.2 Label elements

Labelling according to GHS

Precautionary statements

P280	Wear protective gloves and eye/face protection.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.		
P501	Dispose of contents/container to hazardous or special waste collection point.		
Special rules for supplemental label elements for certain mixtures			

Special rules for supplemental label elements for certain rEUH210Safety data sheet available on request.

(EN / NZ)

Trade name : Revision date : Print date : Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020

Version :

1.0.0

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Periomat Intra/C+ Fixer concentrate contains ammonium thiosulfate, sodium sulfite, organic acids and auxiliary agents in aqueous solution.

Hazardous ingredients

ACETIC ACID ; REACH No. : 01-2119475328-30 ; EC No. : 200-580-7; CAS No. : 64-19-7

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash with plenty of water. When in doubt or if symptoms are observed, get medical advice.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed No information available.

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder Water spray jet Water mist The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

None known.

Hazardous combustion products

None known.

5.3 Advice for firefighters

Trade name : Revision date : Print date :

09.08.2019 21.07.2020

Periomat Intra/C+ Fixer concentrate

Version :

1.0.0

Adapt protective equipment to surrounding fire.

Special protective equipment for firefighters

Adapt protective equipment to surrounding fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Personal protection equipment

See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Other information

Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep/Store only in original container. Please note safety instructions and directions for use on the drum. Handle and open container with care. Provide adequate ventilation. Do not breathe vapour/aerosol.

Protective measures

Measures to prevent fire

Usual measures for fire prevention. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Do not store in temperatures below 5 °C.

Hints on joint storage

Store the foodstuffs separately.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ACETIC ACID ; CAS No. : 64-19-7

 Limit value type (country of origin) :
 STEL (EC)

 Limit value :
 20 ppm / 50 mg/m³

 Version :
 20.06.2019

 Limit value type (country of origin) :
 STEL (EC)

Trade name : Revision date :	Periomat Intra/ 09.08.2019	C+ Fixer concentrate	Version :	1.0.0
Print date :	21.07.2020			1.0.0
Limit value :		50 mg/m ³ / 20 ppm		
Version :				
Limit value type (coun	try of origin) :			
Limit value : Version :		10 ppm / 25 mg/m ³ 20.06.2019		
Limit value type (coun	try of origin) :			
Limit value : Version :	ary or origin).	25 mg/m ³ / 10 ppm		
Limit value type (coun	trv of origin) :	TLV/STEL (NZ)		
Limit value : Version :	, e. e. <u>.</u> g, .	15 ppm / 37 mg/m ³		
Limit value type (coun	try of origin) :	TLV/TWA (NZ)		
Limit value : Version :	, , ,	10 ppm / 25 mg/m ³		
DNEL-/PNEC-val	ues			
There are no data ava		reparation itself.		
DNEL/DMEL				
ACETIC ACID ; CAS No	o.:64-19-7			
Limit value type :		DNEL Consumer (local)		
Exposure route :		Inhalation		
Exposure frequency	·:	Long-term		
Limit value :		25 mg/m ³		
Limit value type :		DNEL Consumer (local)		
Exposure route :		Inhalation		
Exposure frequency	· :	Short-term		
Limit value :		25 mg/m ³		
Limit value type : Exposure route :		DNEL worker (local) Inhalation		
Exposure frequency	, .	Long-term		
Limit value :	•	25 mg/m ³		
Limit value type :		DNEL worker (local)		
Exposure route :		Inhalation		
Exposure frequency	· :	Short-term		
Limit value :		25 mg/m ³		
PNEC				
ACETIC ACID ; CAS No	o.:64-19-7			
Limit value type :		PNEC (Aquatic, freshwater)		
Limit value :		3,058 mg/l		
Limit value type : Limit value :		PNEC (Aquatic, marine water) 0,3058 mg/l		
Limit value type :		PNEC (Industrial)		
Exposure route :		Soil		
Limit value :		0,478 mg/kg		
Limit value type :		PNEC (Sediment, freshwater)		
Limit value :		11,36 mg/kg		
Limit value type :		PNEC (Sediment, marine water)		
Limit value :		1,136 mg/kg		
Limit value type :		PNEC (Sewage treatment plant)		
Limit value :		85 mg/l		
.2 Exposure controls				
Personal protect		nent		
Eye/face protec	tion			
Eye glasses with side	protection DI	N EN 166 per Australian Standard AS 1336 and .	AS/NZS 1337. Safety glasses wit	th side
		$\mathbf{D}_{\mathbf{D}_{\mathbf{C}_{\mathbf{C}}}}$		
		Page : 4 / 10		(FN / N

(EN / NZ)

Trade name : Revision date : Print date : Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020

Version :

1.0.0

shields

Skin protection

Hand protection

Short-term exposure (Level 2: < 30 min): disposable gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.1 mm.

Long-term exposure (Level 6: < 480 min): protective gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.7 mm.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. AUS/NZ: Wear impervious rubber gloves (AS2161).

Body protection

Body protection: not required.

Respiratory protection

Usually no personal respirative protection necessary.

General information

Keep away from food, drink and animal feedingstuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing. Wash hands before breaks and after work. Separate storage of work clothes. When using do not eat, drink, smoke, sniff.

Other protection measures

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance :	Liquid					
Colour :	colourless					
Odour :	Acetic acid					
Safety charact	teristics					
Melting point/free	zing point :	(1013 hPa)		not determined		
Initial boiling point and boiling range :		(1013 hPa)		not determined		
Decomposition ten	nperature :	(1013 hPa)		not determined		
Flash point :				not applicable		
Auto-ignition temp	perature :			not applicable		
Lower explosion li	mit :			not applicable		
Upper explosion lin	mit :			not applicable		
Vapour pressure :		(50 °C)		not determined		
Density :		(20 °C)		1,169 - 1,185	g/cm ³	
Solvent separation	test :	(20 °C)	<	3	%	
Water solubility :		(20 °C)		100	Wt %	
рН :				4,82 - 4,96		
log P O/W :				not determined		
Flow time :		(20 °C)	<	20	S	DIN-cup 4 mm
Odour threshold :				not determined		
Maximum VOC con	itent (EC) :			2,6	Wt %	
Oxidising liquids :		Not applicable.				
Explosive propertie	es :	Not applicable.				
Corrosive to metals :		Not corrosive to	metals.			
Other informat	ion					

None

9.2

SECTION 10: Stability and reactivity

10.1 Reactivity

Trade name : Revision date : Print date :	Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020	Version :	1.0.0

None, if handled according to order.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7). Exothermal reaction with alkalis.

10.3 Possibility of hazardous reactions Exothermal reaction with alkalis.

10.4 Conditions to avoid No information available.

10.5 Incompatible materials None known.

10.6 Hazardous decomposition products None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity	
Acute oral toxicity	
Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	3310 mg/kg
Practical experience/human	evidence
Avoid contact with skin and eye	5.
Acute dermal toxicity	
Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	not relevant
Parameter :	LD50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	1060 mg/kg
Acute inhalation toxicity	
Parameter :	ATEmix calculated
Exposure route :	Inhalation (vapour)
Effective dose :	not relevant
Parameter :	LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route :	Inhalation
Species :	Mouse
Effective dose :	5620 mg/l
Parameter :	LD50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	4000 mg/l
CMR effects (carcinogeni	city, mutagenicity and toxicity for reproduction)
	· · · · · · · · · · · · · · · · · · ·

Based on available data, the classification criteria are not met.

11.5 Additional information

The classification was carried out according to the calculation method of GHS.

SECTION 12: Ecological information

Trade name : Revision date : Print date : Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020

Version :

1.0.0

Aquatic toxicity	
Acute (short-term) fish toxicity	
Parameter :	LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Species :	Leuciscus idus (golden orfe)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	400 - 500 mg/l
Exposure time :	48 h
Parameter :	LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Species :	Lepomis macrochirus (Bluegill)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	75 mg/l
Exposure time :	96 h
Parameter :	LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	79 mg/l
Exposure time :	96 h
Acute (short-term) toxicity to o	
Parameter :	EC50 (ACETIC ACID ; CAS No. : 64-19-7)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	95 mg/l
Exposure time :	24 h
Acute (short-term) toxicity to a	aquatic algae and cyanobacteria
Parameter :	EC0 (ACETIC ACID ; CAS No. : 64-19-7)
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	65 mg/l
Exposure time :	85 h
Toxicity to microorganisms	
Parameter :	EC0 (ACETIC ACID ; CAS No. : 64-19-7)
Species :	Pseudomonas putida
Evaluation parameter :	Bacteria toxicity
Effective dose :	2850 mg/l
Exposure time :	16 h
² Persistence and degradabi	
_	
Biodegradation	
No data available.	
.3 Bioaccumulative potential	
No information available.	
4 Mobility in soil	
-	
Distribution	
There are no data available on the	preparation itself.
^{.5} Results of PBT and vPvB as	ssessment
	t meet the PBT/vPvB criteria according to REACH, annex XIII.
 6 Other adverse effects 	
No information available.	
.7 Additional ecotoxicological	l information
Do not allow to enter into surface wa	

Trade name : Revision date : Print date : Periomat Intra/C+ Fixer concentrate 09.08.2019 21.07.2020

Version :

1.0.0

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Disposal operations

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal.

Recovery operations

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Contact a specialist disposal company or the local waste regulator for advice. This should be done in accordance with 'The Hazardous Waste Act'. Can be eliminated with domestic garbage on condition it complies with local regulations.

Waste codes/waste designations according to EWC/AVV

Concentrate/larger quantities: 09 01 04* fixer solutions.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code not applicable

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

EPA NZ Classes of hazardous properties none

NZ HSNO Approval: HSR006698: Ammonium thiosulfate, HSNO Approval: HSR003212: Sodium sulfite **Restrictions of occupation**

None

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimates

CAS = Chemical Abstracts Service

Trade name :	Periomat Intra/C+ Fixer concentrate		
Revision date :	09.08.2019	Version :	1.0.0
Print date :	21.07.2020		

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CMR = Carcinogen, Mutagen or Reproductive toxicant CO₂ = Carbon dioxide DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EC = European Commission EC50 = Half maximal effective concentration EN = European Standard (Norm) EU = European Union EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals H statement = GHS Hazard statement IATA = International Air Transport Association ICAO-TI = International Civil Aviation Organization-Technical Instructions IMDG = International Maritime Dangerous Goods LC50 = Median lethal concentration LD50 = Median lethal dose LogPow = Logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOEC/NOEL = No observed effect concentration/level OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RMM = Risk Management Measure RRN = REACH Registration Number STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure SVHC = Substances of Very High Concern TLV/STEL = Threshold limit value/short-term exposure limit TLV/TWA = Threshold limit value/time weighted average UN = United Nations VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative 16.3 Key literature references and sources for data Standard EN420:2003 General requirements for protective gloves: disposable gloves, e.g. nitrile rubber, material thickness 0.1 mm (Australian Standard 2161). Long-term exposure (Level 6: < 480 min): protective gloves, e.g. nitrile rubber, material thickness 0.7 mm (Australian Standard 2161). Personal eye protection - Eye and face protectors for occupational applications: safety glasses (Australian Standard AS 1336 and AS/NZS 1337.1:2010). 16.4 Classification for mixtures and used evaluation method according to GHS The classification was carried out according to the calculation method of GHS. 16.5 Relevant H- and EUH-phrases (Number and full text) H226 Flammable liquid and vapour. H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. 16.6 Training advice None 16.7 Additional information Notice the directions for use on the label. The above information describes exclusively the safety requirements of the product and is based on our present-day

Trade name :	Periomat Intra/C+ Fixer concentrate		
Revision date :	09.08.2019	Version :	1.0.0
Print date :	21.07.2020		

sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.