Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master ivory 1957 0200

Renfert GmbH

Revision date: 13.11.2020	Product code: 19570200_AUS_IV	Page 1 of 7
SECTION 1: Identification	n of the substance/mixture and of the company/undertaking	g
1.1. Product identifier		
die:master ivory	1957 0200	
Further trade names		
contained in: 1957 1	000 die:master Set ivory	
	s of the substance or mixture and uses advised against	
Use of the substance/mi	ixture	
One-pack coating		
Uses advised against		
No information availa	able.	
1.3. Details of the supplier of	of the safety data sheet	
Manufacturer		
Company name:	Renfert GmbH	
Street:	Untere Giesswiesen 2	
Place:	D-78247 Hilzingen	
Telephone:	+49 7731 8208-0	Telefax: +49 7731 8208-70
e-mail:	info@renfert.com	
Internet:	www.renfert.com	
Supplier		
Company name:	Ivoclar Vivadent Pty. Ltd.	
Street:	1-5 Overseas Drive	
Place:	- Noble Park North VIC 3174	
Telephone:	+ 61 3 9795 9599	Telefax: + 61 3 9795 9645
.4. Emergency telephone n	number: 131 126 (Poisons Information Centre - 24 hours / 7)	days)
Hazard Statements: Highly flammable liqu Causes serious eye May cause drowsine 2.2. Label elements Regulation (EC) No. 1272/ Hazard components for	irritation. ess or dizziness. 2008	
ethyl acetate	5	
-	Danger	
Signal word:	Danger	
Pictograms:		
Hazard statements	✓ ▼	
H225	Highly flammable liquid and vapour.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
Precautionary statemen	ts	
P210	Keep away from heat, hot surfaces, sparks, open flames and oth	er ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	-
P280	Wear protective gloves and eye/face protection.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
Special labelling of certa		
EUH066	Repeated exposure may cause skin dryness or cracking.	
2.3. Other hazards		
<u>2.3. Other hazards</u> The substances in th	ne mixture do not meet the PBT/vPvB criteria according to REACH, a	annex XIII.

1957 0200

according to Regulation (EC) No 1907/2006

die:master ivory

Revision date: 13.11.2020

Product code: 19570200_AUS_IV

Page 2 of 7

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization One-pack coating

Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	GHS Classification	GHS Classification				
141-78-6	ethyl acetate	50 - 80 %				
	205-500-4	607-022-00-5	01-2119475103-46			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066					
123-86-4	n-butyl acetate			10 - < 30 %		
	204-658-1	607-025-00-1	01-2119485493-29			
	Flam. Liq. 3, STOT SE 3; I	H226 H336 EUH066				
Full toxt of L	- and ELIH statements: see s	action 16		•		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur:

Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

according to Regulation (EC) No 1907/2006

die:master ivory

Revision date: 13.11.2020

Product code: 19570200 AUS IV

1957 0200

Page 3 of 7

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: Butyl caoutchouc (butyl rubber), CR (polychloroprene, chloroprene rubber), PVC (polyvinyl chloride) Thickness of the glove material: 0,5 mm

Breakthrough time: >= 8 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Usually no personal respirative protection necessary.

Provide adequate ventilation.

Environmental exposure controls

Do not allow to enter into surface water or drains.

			Renfert Gmb	Н
Renfert	Safety Data	a Sheet		
	according to Regulation (EC) No 1907/2006		
	die:master ivory	1957 0200		
evision date: 13.11.2020	Product code: 1957	0200_AUS_IV		Page 4 of 7
ECTION 9: Physical and chemical pro	perties			
.1. Information on basic physical and chem	ical properties			
Physical state:	Liquid			
Colour:	light beige			
Odour:	characteristic			
			Test method	
pH-Value:		not applicable		
Changes in the physical state				
Melting point:		not determined		
Initial boiling point and boiling range:		77 °C		
Flash point:		- 1 °C	DIN 51755 (cc)	
Flammability			ζ, γ	
Solid:		not applicable		
Gas:		not applicable		
Explosive properties				
not explosive.				
Vapours can form explosive mixtures	with air.			
Lower explosion limits:		1,2 vol. %		
Upper explosion limits:		11,5 vol. %		
Ignition temperature:		370 °C		
Auto-ignition temperature				
Solid:		not applicable		
Gas:		not applicable		
Decomposition temperature:		not determined		
Vapour pressure: (at 20 °C)		97 hPa		
Density (at 20 °C):		0,96 - 1,10 g/cm³		
Water solubility:		Immiscible		
Partition coefficient:		not determined		
Viscosity / dynamic:		not determined		
Viscosity / kinematic:		not determined		
Vapour density:		not applicable		
Evaporation rate:		not determined		
Solvent content:	ca. 76 %			

9.2. Other information Solid content:

ca. 20 - 25 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met. Irritation and corrosivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1957 0200

die:master ivory

Revision date: 13.11.2020

Product code: 19570200_AUS_IV

Page 5 of 7

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	FARBE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	PAINT
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

	Renfert Gmb	Η
Renfert	Safety Data Sheet	
	according to Regulation (EC) No 1907/2006	
	die:master ivory 1957 0200	
Revision date: 13.11.2020	Product code: 19570200_AUS_IV	Page 6 of
Marine pollutant:	no	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1263	
14.2. UN proper shipping name:	PAINT	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOU	S: no	
14.6. Special precautions for user	- 6 7 0	
Further information: see sectio		
14.7. Transport in bulk according to Annot applicable	nnex II of Marpol and the IBC Code	
SECTION 15: Regulatory informat	ion	
	regulations/legislation specific for the substance or mixture	
EU regulatory information		
2004/42/EC (VOC):	805,4 g/l	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work	
	protection guideline' (94/33/EC).	
Water hazard class (D):	2 - obviously hazardous to water	
Additional information		
Regulation (EU) 2019/1021 (pe	(Ozone depleting substances): not applicable rsistent organic pollutants): not applicable export and import of hazardous chemicals): not applicable	
SECTION 16: Other information		
Abbreviations and acronyms		
PBT: Persistent, Bioaccumulati	ve and Toxic	
vPvB: very Persistent and very		
	ce (division of the American Chemical Society)	
LD50: lethal dose, 50% LC50: lethal concentration, 50%		
	。 u transport international des marchandises Dangereuses par Route (European Agreement	
	rriage of Dangerous Goods by Road)	
•	ransport international ferroviaire de marchandises Dangereuses (Regulations Concerning	
the International Transport of D IMDG: International Maritime C		
ICAO: International Civil Aviatio	5	
MARPOL: International Conver	tion for the Prevention of Marine Pollution from Ships	
VOC: volatile organic compoun		
	evaluation method according to Regulation (EC) No. 1272/2008 [CLP]	
Classification	Classification procedure	
Flam. Liq. 2; H225	On basis of test data	
Eye Irrit. 2; H319	Calculation method	
STOT SE 3; H336	Calculation method	I
Relevant H and EUH statements (n H225 Highly f	umber and full text) lammable liquid and vapour.	
0,1	able liquid and vapour.	
	serious eye irritation.	
H336 May ca	use drowsiness or dizziness	

H336May cause drowsiness or dizziness.EUH066Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day



according to Regulation (EC) No 1907/2006

	die:master ivory	1957 0200	
Revision date: 13.11.2020	Product code: 19570	200_AUS_IV	Page 7 of 7
knowledge. The information is intended to give you advice about the safe handling of the product named in this safety			

data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1956 0600 die:master duo

Revision date: 12.11.2020

Product code: 19560600 AUS IV

Page 1 of 7

Renfert GmbH

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier 1956 0600 die:master duo Further trade names contained in: 1956 0800 die:master Set red 1956 0900 die:master Set blue 1956 1000 die:master Set gold/silver 1957 1000 die:master Set ivory 1957 2000 die:master Set aqua 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture One-pack coating Uses advised against No information available. 1.3. Details of the supplier of the safety data sheet Manufacturer Company name: Renfert GmbH Street: Untere Giesswiesen 2 Place: D-78247 Hilzingen Telephone: +49 7731 8208-0 Telefax: +49 7731 8208-70 e-mail: info@renfert.com www.renfert.com Internet: Supplier Ivoclar Vivadent Pty. Ltd. Company name: Street: 1-5 Overseas Drive Place: - Noble Park North VIC 3174 Telephone: + 61 3 9795 9599 Telefax: + 61 3 9795 9645 131 126 (Poisons Information Centre - 24 hours / 7 days) 1.4. Emergency telephone number: **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Regulation (EC) No. 1272/2008 Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. 2.2. Label elements Regulation (EC) No. 1272/2008 Hazard components for labelling butanone n-butyl acetate Signal word: Danger Pictograms: Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves and eye/face protection. P337+P313 If eye irritation persists: Get medical advice/attention. Revision No: 1,0 GB - EN Print date: 13.11.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo 1956 0600

Revision date: 12.11.2020

Product code: 19560600 AUS IV

Page 2 of 7

Renfert GmbH

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

One-pack coating

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification		÷	
78-93-3	butanone			> 60 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			10 - < 30 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3;	H226 H336 EUH066		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Use personal protection equipment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1956 0600 die:master duo

Revision date: 12.11.2020

Product code: 19560600 AUS IV

Page 3 of 7

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Avoid contact with eyes and skin.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control diaits

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo	1956 0600

Revision date: 12.11.2020

Product code: 19560600_AUS_IV

Page 4 of 7

together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. **Respiratory protection**

respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
		Test method
pH-Value:	not a	pplicable
Changes in the physical state		
Melting point:	not de	termined
Initial boiling point and boiling range:		79 °C
Flash point:		- 5 °C DIN 51755 (cc)
Flammability		
Solid:	not a	pplicable
Gas:	not a	pplicable
Explosive properties		
not explosive.		
Vapours can form explosive mixtures with	h air.	
Lower explosion limits:	1	,2 vol. %
Upper explosion limits:	11	,5 vol. %
Ignition temperature:		370 °C
Auto-ignition temperature		
Solid:	not a	pplicable
Gas:	not a	pplicable
Decomposition temperature:	not de	termined
Vapour pressure:		101 hPa
(at 20 °C)		
Density (at 20 °C):	0,78 - 0,	88 g/cm³
Water solubility:	Im	nmiscible
Partition coefficient:	not de	termined
Viscosity / dynamic:	not de	termined
Viscosity / kinematic:	not de	termined
Evaporation rate:	not de	termined
2 Other information		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No special measures are necessary.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo 1956 0600

Revision date: 12.11.2020

Product code: 19560600_AUS_IV

Page 5 of 7

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
78-93-3	butanone				
	OECD 301D	98 %	28		

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	FARBE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

	Renfert Gmb	4
Renfert	Safety Data Sheet	
	according to Regulation (EC) No 1907/2006	
	die:master duo 1956 0600	
Revision date: 12.11.2020	Product code: 19560600_AUS_IV	Page 6 of 7
	*	
	3	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1263	
14.2. UN proper shipping name:	PAINT	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
	No. Contraction of the second s	
Manufactory and Hada and	3	
Marine pollutant:	no	
Air transport (ICAO-TI/IATA-DGR)	101 1000	
14.1. UN number:	UN 1263	
14.2. UN proper shipping name:	PAINT	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
	*	
	3	
14.5. Environmental hazards ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user		
Further information: see section 6, 7,	, 8	
14.7. Transport in bulk according to Annex I	l of Marpol and the IBC Code	
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture	
EU regulatory information		
2004/42/EC (VOC):	749,3 g/l	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work	
Motor borond along (D):	protection guideline' (94/33/EC).	
Water hazard class (D):	1 - slightly hazardous to water	
Additional information		
Regulation (EC) No 1005/2009 (Ozor Regulation (EU) 2019/1021 (persister	ne depleting substances): not applicable	
	and import of hazardous chemicals): not applicable	
SECTION 16: Other information	· · · · · · · · · · · · · · · · · · ·	
Abbreviations and acronyms		
PBT: Persistent, Bioaccumulative and	1 Toxic	
vPvB: very Persistent and very Bioac		
CAS: Chemical Abstracts Service (div	vision of the American Chemical Society)	
LD50: lethal dose, 50%		
LC50: lethal concentration, 50%	ration	
EC50: half maximal effective concent ADR: Accord européen relatif au tran	ration sport international des marchandises Dangereuses par Route (European Agreement	
concerning the International Carriage		
	ort international ferroviaire de marchandises Dangereuses (Regulations Concerning	
the International Transport of Danger	ous Goods by Rail)	
IMDG: International Maritime Code for		
ICAO: International Civil Aviation Org		



according to Regulation (EC) No 1907/2006

die:master duo 1956 0600

Revision date: 12.11.2020

Product code: 19560600 AUS IV

Page 7 of 7

Renfert GmbH

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure			
Flam. Liq. 2; H225	On basis of test data			
Eye Irrit. 2; H319	Calculation method			
STOT SE 3; H336	Calculation method			
Relevant H and FIIH statements (number and full text)				

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Renfert GmbH

Page 1 of 7

Renfert Safety Data Sheet according to Regulation (EC) No 1907/2006 die:master thinner 1956 0700 Revision date: 13.11.2020 Product code: 19560700 AUS IV SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier die:master thinner 1956 0700 Further trade names contained in: 1956 0800 die:master Set red 1956 0900 die:master Set blue 1956 1000 die:master Set gold/silver 1957 1000 die:master Set ivory 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture die master thinner Uses advised against No information available. 1.3. Details of the supplier of the safety data sheet Manufacturer Company name: Renfert GmbH Street: Untere Giesswiesen 2 Place: D-78247 Hilzingen +49 7731 8208-0 Telephone: Telefax: +49 7731 8208-70 e-mail: info@renfert.com www.renfert.com Internet: Supplier Ivoclar Vivadent Pty. Ltd. Company name: 1-5 Overseas Drive Street: Place: - Noble Park North VIC 3174 Telephone: + 61 3 9795 9599 Telefax: + 61 3 9795 9645 131 126 (Poisons Information Centre - 24 hours / 7 days) 1.4. Emergency telephone number: **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Regulation (EC) No. 1272/2008 Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. 2.2. Label elements Regulation (EC) No. 1272/2008 Hazard components for labelling butanone pentan-3-one

n-butyl acetate

Hazard statements H225

H319

H335

H336

Danger

Signal word:

Pictograms:

Highly flammable liquid and vapour.

Safety Data Sheet

Renfert GmbH

according to Regulation (EC) No 1907/2006

die:master thinner 1956 0700

Revision date: 13.11.2020

Product code: 19560700 AUS IV

Page 2 of 7

Precautionary statements

······································						
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.					
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.					
P280	Wear protective gloves and eye/face protection.					
P337+P313	If eye irritation persists: Get medical advice/attention.					
P403+P233	Store in a well-ventilated place. Keep container tightly closed.					
Special labelling of certain mixtures						
EUH066	Repeated exposure may cause skin dryness or cracking.					

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Solvents/Thinner

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	-	•		
78-93-3	butanone			50 - 70 %	
	201-159-0	606-002-00-3	01-2119457290-43		
	Flam. Liq. 2, Eye Irrit. 2, S				
96-22-0	pentan-3-one	20 - 40%			
	202-490-3	606-006-00-5	01-2119531111-60		
	Flam. Liq. 2, Eye Irrit. 2, S				
123-86-4	n-butyl acetate	5 - 15%			
	204-658-1	607-025-00-1	01-2119485493-29		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.



according to Regulation (EC) No 1907/2006

die:master thinner 1956 0700

Revision date: 13.11.2020

Product code: 19560700 AUS IV

Page 3 of 7

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Use personal protection equipment.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Avoid contact with eyes and skin. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
96-22-0	Pentan-3-one	200	716		TWA (8 h)	WEL
		250	895		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour.

Avoid contact with skin, eyes and clothes.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master thinner 1956 0700

Revision date: 13.11.2020

Product code: 19560700_AUS_IV

Page 4 of 7

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid		
Colour:	colourless		
Odour:	characteristic		
			Test method
pH-Value:		not applicable	
Changes in the physical state			
Melting point:		not determined	
Initial boiling point and boiling range	je:	79 °C	
Flash point:		- 1,5 °C	DIN 51755 (cc
Flammability			
Solid:		not applicable	
Gas:		not applicable	
Explosive properties			
not explosive.			
Vapours can form explosive m	ixtures with air.		
Lower explosion limits:		1,2 vol. %	
Upper explosion limits:		11,5 vol. %	
Ignition temperature:		370 °C	
Auto-ignition temperature			
Solid:		not applicable	
Gas:		not applicable	
Decomposition temperature:		not determined	
Vapour pressure:		105 hPa	
(at 20 °C) Density (at 20 °C):		0,7 - 0,9 g/cm³	
Water solubility:		Immiscible	
Partition coefficient:		not determined	
Viscosity / dynamic:		not determined	
Viscosity / kinematic:		not determined	
Vapour density:		not determined	
Evaporation rate:		not determined	
Solvent content:	100%		
Other information			
Solid content:	0 %		

SECTION 10: Stability and reactivity

Safety Data Sheet

Renfert GmbH

according to Regulation (EC) No 1907/2006

die:master thinner 1956 0700

Product code: 19560700_AUS_IV

Page 5 of 7

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

Revision date: 13.11.2020

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (pentan-3-one)

May cause drowsiness or dizziness. (butanone; pentan-3-one)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name					
	Method		Value	d	Source	
	Evaluation					
78-93-3	butanone					
	OECD 301D		98 %	28		
	Readily biodegradable (according to OECD criteria).					

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow	
96-22-0	pentan-3-one	0,82	

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow

Page 6 of 7

Renfert	Safety Data	Sheet
	according to Regulation (EC)	
	die:master thinner	1956 0700
Revision date: 13.11.2020	Product code: 195607	700_AUS_IV
uncontrolled discharge of product in	to the environment.	
SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Disposal recommendations		
Dispose of waste according to appli	cable legislation.	
Contaminated packaging		
Handle contaminated packages in the	ne same way as the substance itsel	f.
SECTION 14: Transport information		
Land transport (ADR/RID)		
<u>14.1. UN number:</u>	UN 1263	
14.2. UN proper shipping name:	FARBZUBEHÖRSTOFFE	

14.2. UN proper shipping name:	FARBZUBEHÖRSTOFFE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	PAINT RELATED MATERIAL
14.3. Transport hazard class(es):	3
14.4. Packing group:	Ш
Hazard label:	3
Marine pollutant:	no
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	PAINT RELATED MATERIAL
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	no
14.6. Special precautions for user Additional information: see section 6, 7, 8	

14.2. UN proper shipping name:	PAINT RELATED MATERIAL	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user		
Additional information: see section 6, 7, 8		
14.7. Transport in bulk according to Annex II of M	Marpol and the IBC Code	
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulation	ns/legislation specific for the substance or mixture	
EU regulatory information		
2004/42/EC (VOC):	100 %	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'ju protection guideline' (94/33/EC).	venile work
Water hazard class (D):	1 - slightly hazardous to water	
Additional information		
Regulation (EC) No 1005/2009 (Ozone de	pleting substances): not applicable	
Revision No: 1,0	GB - EN	Print date: 13.11.2020



according to Regulation (EC) No 1907/2006

die:master thinner 1956 0700

Revision date: 13.11.2020

Product code: 19560700_AUS_IV

Page 7 of 7

Regulation (EU) 2019/1021 (persistent organic pollutants): not applicable

Regulation (EU) No 649/2012 (export and import of hazardous chemicals): not applicable

SECTION 16: Other information

Abbreviations and acronyms

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning

the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)