



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Stabiloplast Resin 448 0003

Further trade names

448 0004 Stabiloplast Set

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Renfert GmbH	
Street:	Untere Giesswiesen 2	
Place:	D-78247 Hilzingen	
Telephone:	+49 7731 8208-0	Telefax: +49 7731 8208-70
e-mail:	info@renfert.com	
Contact person:	Frau Andris	Telephone: +49 7731 8208-927
e-mail:	silke.andris@renfert.com	
Internet:	www.renfert.com	

1.4. Emergency telephone number:

GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA: 800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 New Foundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021 931 6129 (24 Hours)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl 2-cyanoacrylate

Signal word: Warning**Pictograms:****Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P337+P313 If eye irritation persists: Get medical advice/attention.

Special labelling of certain mixtures

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 2 of 7

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Cyanoacrylate containing adhesive.

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
7085-85-0	ethyl 2-cyanoacrylate			50 - 100 %
	230-391-5	607-236-00-9	01-2119527766-29	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
123-31-9	1,4-dihydroxybenzene			< 0,1 %
	204-617-8	604-005-00-4		
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 1); H351 H341 H302 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take off contaminated clothing and wash it before reuse.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Extinguishing powder, Carbon dioxide (CO₂), alcohol resistant foam, Water spray jet**Unsuitable extinguishing media**

Full water jet

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment.

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Allow stiffening. Take up mechanically.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 3 of 7

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Handle and open container with care.
- Use only in well-ventilated areas.
- Avoid contact with eyes and skin.
- When using do not eat, drink or smoke.

Advice on protection against fire and explosion

- No special fire protection measures are necessary.

Further information on handling

- If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep only in the original container in a cool, well-ventilated place.
- Keep container tightly closed.

Advice on storage compatibility

- No special measures are necessary.

Further information on storage conditions

- storage temperature: 10°C
- Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

- Please refer to our internet website for more information: www.renfert.com

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7085-85-0	Ethyl cyanoacrylate	-	-	-	TWA (8 h)	WEL
		0.3	1.5		STEL (15 min)	WEL
123-31-9	Hydroquinone	-	0.5	-	TWA (8 h)	WEL
		-	-	-	STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

- Safe handling: see section 7

Protective and hygiene measures

- Do not breathe vapour.
- Avoid contact with skin, eyes and clothes.
- Wash hands before breaks and after work.
- Keep away from food, drink and animal feedingstuffs.

Eye/face protection

- Wear eye/face protection.

Hand protection

- When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
- Suitable material: NBR (Nitrile rubber)
- Thickness of the glove material: 0,5 mm
- Breakthrough time: > 30 min
- For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

- If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
- Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

- Do not allow to enter into surface water or drains.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 4 of 7

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: blue
Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not determined
Initial boiling point and boiling range: 150 °C Literaturwert
Flash point: 87 °C DIN 51758

Explosive properties

not explosive according to EU A.14

Lower explosion limits: not determined
Upper explosion limits: not determined
Ignition temperature: not determined
Decomposition temperature: not determined
Vapour pressure: 0,3 hPa
(at 20 °C)
Density: not determined
Water solubility: practically insoluble
Partition coefficient: not determined
Viscosity / dynamic: not determined
Viscosity / kinematic: not determined
Vapour density: not determined
Solvent content: 0,0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Alcohols, Amines, Alkali (lye), Acid, Water

10.4. Conditions to avoid

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 5 of 7

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7085-85-0	ethyl 2-cyanoacrylate				
	oral	LD50 > 5000 mg/kg	Rat		OECD 401
	dermal	LD50 > 2000 mg/kg	Rabbit		OECD 402
123-31-9	1,4-dihydroxybenzene				
	oral	LD50 375 mg/kg	Rat		OECD 401
	dermal	LD50 > 2000 mg/kg	Rabbit		OECD 402

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information**12.1. Toxicity**

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.
The product has not been tested. Due to the consistency along with the low water solubility of the product a bioavailability is unlikely.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 6 of 7

Land transport (ADR/RID)**Other applicable information (land transport)**

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): not applicable

National regulatory information

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethyl 2-cyanoacrylate

SECTION 16: Other information**Changes**

Abs. 4, 13, 15, 16 * Data changed compared with the previous version

Abbreviations and acronyms

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Resin 448 0003

Revision date: 11.04.2018

Product code: 4480003

Page 7 of 7

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)